



# 技术参数

technical parameter

DM-EA1117A

## 1、电气性能 Electrical Characteristics

测试条件: 25±2℃, 湿度 25%~75%, 气压值 86kPa~106kPa

Test conditions: 25±2℃, humidity 25%~75%, air pressure 86kPa~106kPa

编号 NO	项目 Items	规格 Specification	备注 Notes
1	直流电阻 DC resistance	7.4±7% Ω	
2	绝缘电阻 Insulation resistance	≥10MΩ	测试电压 100VDC, 产品端子和外壳之间的绝缘电阻 100V DC input, between Case and Pad
3	磁感应强度-1(直流 2V) Magnetic induction intensity - 1 (DC 2V)	365±9% mT	接触式测量磁感应强度最大值; 音圈供给测试信号: 正向直流 2V Contact type measurement of maximum magnetic induction intensity; Voice coil supply test signal: forward DC 2V
4	磁感应强度-2 (不通电) Magnetic induction intensity - 2 (without power)	380±9% mT	接触式测量磁感应强度最大值; Contact type measurement of maximum magnetic induction intensity;
5	磁场极性 Magnetic field polarity		靠近外壳面为 S 极; 磁铁表面为 N 极; S pole near the housing surface;The surface of the magnet is N-pole

2、产品外形图 Product Drawing

